

TOYOTA NOAH SPECIFICATIONS



	HYBRID			Gasoline						"Side Lift-up Tilt Seat"	
	Si	G	X	Si	8	G	X	8			
Seating Capacity	7			7	8	7	8	7	8	7	
Number	3	5		3				5			
Model, Weight & Performance											
Model	2WD (Front Wheel Drive)	DAA-ZWR80W -APXSB★	DAA-ZWR80G -APXGB★	DAA-ZWR80G -APXEB★	DBA-ZRR80W -APXSP■	DBA-ZRR80W -ARXSP■	DBA-ZRR80G -APXGP■	DBA-ZRR80G -ARXGP■	DBA-ZRR80G -APXEP■	DBA-ZRR80G -ARXEP■	DBA-ZRR80G -APXEP(W)■
	4WD	-	-	-	DBA-ZRR85W -APXSP■	DBA-ZRR85W -ARXSP■	DBA-ZRR85G -APXGP■	DBA-ZRR85G -ARXGP■	DBA-ZRR85G -APXEP■	DBA-ZRR85G -ARXEP■	DBA-ZRR85G -APXEP(W)■
Weight*1	kg	1,620*2	1620*3	1,610*2*3	1,600[1,680]*2*4*5		1,570[1,660]*2*4*5		1,570[1,650]*2		1,650[1,730]
Total weight*1	kg	2,005*2	2005*3	1,995*2*3	1,985[2,065] *2*4*5	2,040[2,120] *2*4*5	1,955[2,045] *2*4*5	2,010[2,100] *2*4*5	1,955[2,035]*2	2,010[2,090]*2	2,035[2,115]
Minimum turning radius	m	5.5									
Fuel consumption JC08 mode (Ministry-audited)	km / L	23.8			16.0[14.8]			16.0[15.0*6]		16.0*7[14.8]	
Major fuel consumption improvement measures		Hybrid system, Idling stop device, Electric continuously variable transmission, Variable valve timing, Electric power steering,			Idling stop device, Super continuously variable transmission, Charging control, Variable valve timing, Electric power steering						
Dimensions											
Total length	mm	4,710	4,695		4,710				4,695		
Total width	mm	1,735	1,695		1,735				1,695		
Total height	mm	1,825			1,825[1,870]				1,825[1,865]		
Wheelbase	mm				2,850						
Tread Front/Rear	mm	1,500/1,480	1,480/1,480		1,500/1,480			1,480/1,475[1,480]			
Minimum ground clearance*8	mm	160						160[155]			
Interior length x width x height*8	mm	2,930 x 1,540 x 1,400			2,930 x 1,540 x 1,400*9					2,930 x 1,540 x 1,400	
Engine											
Model		2ZR-FXE			3ZR-FAE						
Total displacement	L	1.797			1.986						
Type					Inline 4-cylinder DOHC						
Bore x Stroke	mm	80.5 x 88.3			80.5 x 97.6						
Fuel used		Unleaded regular gasoline									
Maximum output (net)	kW [PS] / r.p.m.	73 (99) / 5,200			112 (152) / 6,100						
Maximum torque (net)	N.m [kgf.m] / r.p.m.	142 (14.5) / 4,000			193 (19.7) / 3,800						
Fuel supply device		EFI (electronic fuel injection)									
Fuel tank capacity	L	50			55						
Traveling device											
Suspension	Front/Rear	Macpherson strut coil spring/Torsion beam coil spring									
Brake	Front/Rear	Ventilated discs				Ventilated discs/leading trailing drum [discs]					
	Operating system	Hydraulic cooperative regenerative brakes				Hydraulic					
Transmission, gear ratio & reduction ratio											
Transmission		Electric continuously variable transmission				Super CVT-I (Super continuously variable transmission / 7-speed sequential shift-matic)					
Forward		-				2.517~0.390					
Reverse		-				1.751					
Reduction ratio		3.703				5.182[5.470]					
Motor											
Model		5JM									
Type		AC synchronous motor									
Maximum torque	kW [Ps]	60 (82)									
Maximum torque (net)	N.m [kgf.m]	207 (21.1)									
Main battery for power											
Type		Nickel Metal Hydride Battery									
Capacity	Ah	6.5									

[] refers to 4WD. *1. Add 10kg if SRS side airbags + SRS curtain shield airbags are installed. *2. Add 10kg if rear auto aircon is installed. *3. Add 10kg if accessory socket is installed. *4. Add 10kg if T-Connect SD navigation system is installed. *5. Add 20kg if twin moonroof (except G 4WD[8-seater]) is installed. *6. 14.8km/L if weight exceeds 1,660kg due to installation of manufacturer's options for X(4WD). *7. 15.2km/L if weight exceeds 1,660kg due to installation of manufacturer's options for X"Side Lift-up Tilt Seat"(2WD). *8. Measured internally. *9. 1,365mm if twin moonroof (except G 4WD[8-seater]) is installed.

Fuel consumption is based on established test conditions. It may differ based on customer's usage environment (weather, traffic, etc.) and driving habits (sudden acceleration, air-conditioner usage, etc.).

Engine power can be displayed either in net value or gross value. "Gross" is based only on engine measurement while "Net" is based on engine measurement under similar conditions when the vehicle is laden. When measured with the same engine, "Net" will be approximately 15% lower than "Gross" for gasoline vehicle (as measured by Japan Automobile Manufacturers Association).

★ refer to vehicles that fall under "Tax Incentives to Promote the Use of Environment Friendly vehicles". ★ Purchasers enjoy reduced automobile acquisition tax (effective till 31 March 2019). In addition, purchasers enjoy reduce automobile weight tax (applicable only to new vehicles registered before 30 April 2019). ■ Purchasers enjoy reduced automobile acquisition tax (effective till 31 March 2018). In addition, purchasers enjoy reduce automobile weight tax (applicable only to new vehicles registered before 30 April 2018). ★ Vehicles marked will be subject to reduced vehicle tax in the following year after purchase (applicable only to new vehicles registered before 31 March 2018). Please enquire with the dealer for details.

■ "NOAH", "HYBRID SYNERGY DRIVE", "VALVEMATIC", "OPTITRON", "VVT-i", "VSC", "TRC", "ECB", "EFI", "Sound Library", "TOYOTA SAFETY SENSE", "TSOP", "T-Connect", "Welcab" and "TECS" are trademarks of Toyota Motor. ■ Values of vehicle model specification in the application form are in accordance with the Road Transport Vehicle Act. ■ Manufacturer: Toyota Motor Corporation. ■ X"Side Lift-up Tilt Seat Car to be sold from Oct 2017.

In accordance with the implementation of the Vehicle Recycling Law, the following recycling fees will be imposed separately.

Model	Deposit for Recycling				Fund Mgt Fee	Total
	Shredder dust fee	Airbags Fee	Freon Fee	Info Mgt Fee		
Whole Vehicle	8,760	1,930	1,650	130	290	12,760

* Recycling deposit money is refundable when the previous owner (transferor) transfers the vehicle, for which the recycling deposit money has been paid, during a sale by receiving from the new owner (transferee) the total amount of the value of the vehicle and the corresponding recycling deposit money. For details, please enquire at the distributor handling the transaction.

Side Lift-up Tilt Seat Specifications

Lift capacity	100kg (exclude seat)
Rotate and Descend Time	30-35 sec
Ascend and Rotate Time	30-35 sec
Minimum Seat Height at Descend	470[490]mm
Seat-Door during Rotation	1,170mm
Feet Space during Rotation	390mm
Seat Slide Forward & Reverse	Forward 167mm Reverse 28mm

[] refers to 4WD
Design values shown. May differ in actual measurement.